

# 14kettle

5000 + 30%1500 .....

---

kettlegploadGreenplum 5.Xkettle7.X

kettleFineReportetlfrkettlekettle

kettlegpload

1gpload kettlegploadyamlFORMATtextNULL\_AStextNULL\_AS\N

2gploadgploadpgsql:1kettlekettle

3gploadgreenplum4.Xgreenplum5.X

43greenplum4.Xgreenplum5.Xkettlegploadgp5.x

gpload [http://gpdb.docs.pivotal.io/500/utility\\_guide/admin\\_utilities/gpload.html](http://gpdb.docs.pivotal.io/500/utility_guide/admin_utilities/gpload.html)

5.0.0gpccjdbch<http://pan.baidu.com/s/1nvBIZdR> cecq

redhat 6.x redhat 7.x centos 6.xcentos 7.x

yaml

--- VERSION: 1.0.0.1 --schema

DATABASE: db\_name --,\$PGDATABASEgpload-d

USER: db\_username --gp\_external\_grant\_privilegeson

HOST: master\_hostname --mastergpload-h\$PGHOST

PORT: master\_port --master5432,gpload-p\$PGPORT

GPLOAD: --INPUT:OUTPUT:

INPUT: ---

SOURCE: --sourcesource

LOCAL\_HOSTNAME: --gploadip -hostname\_or\_ip

PORT: http\_port --gpdfistport | PORT\_RANGE: [start\_port\_range, end\_port\_range]

FILE: --gpzipbzip2\*C - /path/to/input\_file -

COLUMNS: --source - field\_name: data\_type -

FORMAT: text | csv --textcsv -

DELIMITER: 'delimiter\_character' --| -

ESCAPE: 'escape\_character' | 'OFF' --texttext\textoff -

NULL\_AS: 'null\_string' --text\Ncsv -

FORCE\_NOT\_NULL: true | false --csv""0 -

QUOTE: 'csv\_quote\_character' --csv" - HEADER: true | false -- -

ENCODING: database\_encoding -- -

ERROR\_LIMIT: integer --gpload -

ERROR\_TABLE: schema.table\_name --

OUTPUT: - TABLE: schema.table\_name -- -

MODE: insert | update | merge --insertmerge -  
MATCH\_COLUMNS: --updatemerge -  
target\_column\_name - UPDATE\_COLUMNS: --updatemerge -  
target\_column\_name - UPDATE\_CONDITION: 'boolean\_condition' --wheremergeinsert) -  
MAPPING: --source  
target\_column\_name: source\_column\_name | 'expression' PRELOAD: --load -  
TRUNCATE: true | false --true, -  
REUSE\_TABLES: true | false --true  
SQL: - BEFORE: "sql\_command" --SQL - AFTER: "sql\_command" --SQL