

FineReportant

FineReportjarjarbuild.xml

## FineReport

```
plugin-name  
lib  
    fr-core-8.0.jar  
src  
    com.fr.pluing.xxxx  
build.xml  
plugin.xml  
finereportjarlibfr-applet-8.0.jarbuild.xml
```

### build.xml

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>  
<project basedir=". " default="jar" name="plugin">  
    <!-- JDK-->  
    <property name="jdk.home" value="/System/Library/Java/JavaVirtualMachines/1.6.1.jdk/Contents/Home"/>  
  
    <property name="libs" value="${basedir}/lib"/>  
    <property name="publicLibs" value="" />  
    <property name="destLoc" value=". "/>  
    <property name="classes" value="classes"/>  
  
    <xmlproperty file="${basedir}/plugin.xml"/>  
    <property name="current-version" value="${plugin.version}"/>  
  
    <!-- -->  
    <property name="plugin-version" value="${current-version}"/>  
    <!-- -->  
    <property name="plugin-name" value="my-name"/>  
    <property name="plugin-jar" value="fr-plugin-${plugin-name}-${plugin-version}.jar"/>  
  
    <target name="prepare">  
        <delete dir="${classes}"/>  
        <delete dir="fr-plugin-${plugin-name}-${plugin-version}"/>  
        <xmlproperty file="${basedir}/plugin.xml"/>  
        <delete dir="${destLoc}/${plugin.name}"/>  
    </target>  
    <path id="compile.classpath">  
        <fileset dir="${libs}">  
            <include name="**/*.jar"/>  
        </fileset>  
        <fileset dir="${publicLibs}">  
            <include name="**/*.jar"/>  
        </fileset>  
    </path>  
    <patternset id="resources4Jar">  
        <exclude name="**/.settings/**"/>  
        <exclude name=".classpath"/>  
        <exclude name=".project"/>
```

```

<exclude name="**/*.java"/>
<exclude name="**/*.db"/>
<exclude name="**/*.g"/>
<exclude name="**/package.html"/>
</patternset>
<target name="copy_resources">
    <echo message="\${resources_from},JS,CSS"/>
    <delete dir="tmp"/>
    <copy todir="tmp">
        <fileset dir="\${resources_from}\src">
            <patternset refid="resources4Jar"/>
        </fileset>
    </copy>
    <copy todir="\${classes}">
        <fileset dir="tmp"/>
    </copy>
    <delete dir="tmp"/>
</target>
<target name="compile_javas">
    <echo message="\${compile_files}Java"/>
    <javac destdir="\${classes}" debug="false" optimize="on" source="\${source_jdk_version}" target="\${target_jdk_version}" fork="true" memoryMaximumSize="512m" listfiles="false" srcdir="\${basedir}" executable="\${compile_jdk_version}/bin/javac">
        <src path="\${basedir}/src"/>
        <exclude name="**/.svn/**"/>
        <compilerarg line="-encoding UTF8 "/>
        <classpath refid="compile.classpath"/>
    </javac>
</target>

<target name="jar_classes">
    <echo message="Jar:\${jar_name}"/>
    <delete file="\${basedir}/\${jar_name}"/>
    <jar jarfile="\${basedir}/\${jar_name}">
        <fileset dir="\${classes}">
        </fileset>
    </jar>
</target>

<target name="super_jar" depends="prepare">
    <antcall target="copy_resources">
        <param name="resources_from" value="\${basedir}"/>
    </antcall>
    <antcall target="compile_javas">
        <param name="source_jdk_version" value="1.6"/>
        <param name="target_jdk_version" value="1.6"/>
        <param name="compile_jdk_version" value="\${jdk.home}"/>
        <param name="compile_files" value="\${basedir}/src"/>
    </antcall>
    <echo message="compile plugin success!"/>
    <antcall target="jar_classes">
        <param name="jar_name" value="\${plugin-jar}"/>
    </antcall>
    <delete dir="\${classes}"/>
</target>
<target name="jar" depends="super_jar">
    <antcall target="zip"/>
</target>

<target name="zip">
    <property name="plugin-folder" value="fr-plugin-\${plugin-name}-\${plugin-version}"/>
    <echo message="-----zip files-----"/>
    <mkdir dir="\${plugin-folder}"/>
    <copy todir="\${plugin-folder}">
        <fileset dir=". ">
            <include name="\${plugin-jar}"/>
            <include name="plugin.xml"/>

```

```

        </fileset>
    </copy>
    <zip destfile="${basedir}/${plugin-folder}.zip" basedir=".">
        <include name="${plugin-folder}/*.jar"/>
        <include name="${plugin-folder}/plugin.xml"/>
    </zip>
    <xmlproperty file="${basedir}/plugin.xml"/>
    <move file="${plugin-folder}.zip" todir="${destLoc}/${plugin.name}" />
</target>
</project>

```

4jdk.home17plugin-name

build.xmlantIntelliJ IDEAant

```
ant -f build.xml jar
```

## jar

jarlib/reportjarlib

plugin-name

lib

report

fr-core-8.0.jar

other.jar

src

com.fr.plugin.xxxx

build.xml

plugin.xml

## build.xml

```

<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<project basedir=". " default="jar" name="plugin">
    <!-- JDK-->
    <property name="jdk.home" value="/Library/Java/JavaVirtualMachines/jdk1.8.0_40.jdk/Contents/Home" />

    <property name="libs" value="${basedir}/lib"/>
    <property name="publicLibs" value="" />
    <property name="reportLibs" value="${basedir}/lib/report" />
    <property name="destLoc" value=". "/>
    <property name="classes" value="classes" />
    <xmlproperty file="${basedir}/plugin.xml" />
    <property name="current-version" value="${plugin.version}" />

    <!-- -->
    <property name="plugin-version" value="${current-version}" />
    <!-- -->
    <property name="plugin-name" value="my-name" />
    <property name="plugin-jar" value="fr-plugin-${plugin-name}-${plugin-version}.jar" />

    <target name="prepare">
        <delete dir="${classes}" />
        <delete dir="fr-plugin-${plugin-name}-${plugin-version}" />
        <xmlproperty file="${basedir}/plugin.xml" />
        <delete dir="${destLoc}/${plugin.name}" />
    </target>
    <path id="compile.classpath">
        <fileset dir="${libs}" >

```

```

        <include name="**/*.jar"/>
    </fileset>
    <fileset dir="${publicLibs}">
        <include name="**/*.jar"/>
    </fileset>
    <fileset dir="${reportLibs}">
        <include name="**/*.jar"/>
    </fileset>
</path>
<patternset id="resources4Jar">
    <exclude name="**/.settings/**"/>
    <exclude name=".classpath"/>
    <exclude name=".project"/>

    <exclude name="**/*.java"/>
    <exclude name="**/*.db"/>
    <exclude name="**/*.g"/>
    <exclude name="**/package.html"/>
</patternset>
<target name="copy_resources">
    <echo message="\${resources_from},JS,CSS"/>
    <delete dir="tmp"/>
    <copy todir="tmp">
        <fileset dir="\${resources_from}\src">
            <patternset refid="resources4Jar"/>
        </fileset>
    </copy>
    <copy todir="\${classes}">
        <fileset dir="tmp"/>
    </copy>
    <delete dir="tmp"/>
</target>
<target name="compile_javas">
    <echo message="\${compile_files}Java"/>
    <javac destdir="\${classes}" debug="false" optimize="on" source="\${source_jdk_version}" target="\${target_jdk_version}" fork="true" memoryMaximumSize="512m" listfiles="false" srcdir="\${basedir}" executable="\${compile_jdk_version}/bin/javac">
        <src path="\${basedir}/src"/>
        <exclude name="**/.svn/**"/>
        <compilerarg line="-encoding UTF8 "/>
        <classpath refid="compile.classpath"/>
    </javac>
</target>

<target name="jar_classes">
    <echo message="Jar:\$\{jar_name\}" />
    <delete file="\${basedir}/\$\{jar_name\}" />
    <jar jarfile="\${basedir}/\$\{jar_name\}">
        <fileset dir="\${classes}">
        </fileset>
    </jar>
</target>

<target name="super_jar" depends="prepare">
    <antcall target="copy_resources">
        <param name="resources_from" value="\${basedir}" />
    </antcall>
    <antcall target="compile_javas">
        <param name="source_jdk_version" value="1.6" />
        <param name="target_jdk_version" value="1.6" />
        <param name="compile_jdk_version" value="\${jdk.home}" />
        <param name="compile_files" value="\${basedir}/src" />
    </antcall>
    <echo message="compile plugin success!" />

    <antcall target="jar_classes">
        <param name="jar_name" value="\${plugin-jar}" />
    </antcall>
    <delete dir="\${classes}" />

```

```
</target>

<target name="jar" depends="super_jar">
    <antcall target="zip"/>
</target>

<target name="zip">
    <property name="plugin-folder" value="fr-plugin-${plugin-name}-${plugin-version}"/>
    <echo message="-----zip files-----"/>
    <mkdir dir="${plugin-folder}"/>
    <copy todir="${plugin-folder}">
        <fileset dir=".">
            <include name="${plugin-jar}"/>
            <include name="plugin.xml"/>
        </fileset>
        <fileset dir="${libs}">
            <include name="*.jar"/>
            <include name="*.dll"/>
        </fileset>
    </copy>
    <zip destfile="${basedir}/${plugin-folder}.zip" basedir=".">
        <include name="${plugin-folder}/*.jar"/>
        <include name="${plugin-folder}/*.dll"/>
        <include name="${plugin-folder}/plugin.xml"/>
    </zip>
    <move file="${plugin-folder}.zip" todir="${destLoc}/${plugin.name}"/>
</target>
</project>
```

antjar