

com.fr.stable.fun.LocaleFinder

-
-
-
-
-
-
-
-

JS 3

LocaleFinder.java

```
package com.fr.stable.fun;

/**
 * @author richie
 * @date 2015-07-09
 * @since 8.0
 */
public interface LocaleFinder extends Level {

    String MARK_STRING = "LocaleFinder";

    int CURRENT_LEVEL = 1;

    /**
     *
     * @return
     */
    String find();
}
```

FR	8.0		
FR	9.0		
FR	10.0		
BI	3.6		
BI	4.0		
BI	5.1		
BI	5.1.2		

BI	5.1.3		
----	-------	--	--

plugin.xml

```
<extra-core>
    <LocaleFinder class="your class name"/>
</extra-core>
```

```
ExtraClassManager#addLocaleFinder InterProviderFactory InterProvider
InterProviderFactory InterProvider getLocText
```

```
String find(); JAR com/tp tj/demo/hg/locale/demo
properties
com/tp tj/demo/hg/locale/demo com/tp tj/demo/hg/localedemodemo com/tp tj/demo/hg/locale/demo.properties
com/tp tj/demo/hg/locale/demo_zh_CN.properties
```

demo.properties

```
Plugin-Demo_Hello_World=Hello World
Plugin-Demo_Number=number: {}
```

demo_zh_CN.properties

```
Plugin-Demo_Hello_World=
Plugin-Demo_Number=: {}
```

demo_en_US.properties

```
Plugin-Demo_Hello_World=Hello World
Plugin-Demo_Number=number: {}
```

```
//
InterProviderFactory.getDesignI18nProvider().getLocText("Plugin-Demo_Hello_World");
InterProviderFactory.getDesignI18nProvider().getLocText("Plugin-Demo_Number","100");
//
Toolkit.getLocText("Plugin-Demo_Hello_World");
Toolkit.getLocText("Plugin-Demo_Number","100");

//
InterProviderFactory.getProvider().getLocText("Plugin-Demo_Hello_World");
InterProviderFactory.getProvider().getLocText("Plugin-Demo_Number","100");

//
FR.i18nText("Plugin-Demo_Hello_World");
FR.i18nText("Plugin-Demo_Number","100");

//
BI.i18nText("Plugin-Demo_Hello_World");
BI.i18nText("Plugin-Demo_Number","100");
```

⌋

	key
	zh zh_CN
	zh_TW
	en en_US
	ja_JP
	ko_KR

demo[demo-locale-finder](#)

[open-JSD-7944](#)

[open-JSD-7814](#)

[open-JSD-7803](#)

[open-JSD-7706](#)

[open-JSD-6952](#)

[open-JSD-6890](#)