

com.finebi.provider.api.component. CustomComponentProvider

CustomComponentProvider

CustomComponentProvider.java

```
package com.finebi.provider.api.component;

import com.finebi.common.context.OperationContext;
import com.finebi.provider.api.component.data.DataModel;
import com.fr.common.annotations.Open;
import com.fr.stable.fun.mark.Mutable;
import com.fr.web.struct.AssembleComponent;

import java.util.List;

/**
 * <p></p>
 *
 * @author Jimmy.Zheng
 * @since 6.0
 * Created on 2023/5/22
 */
@Open
public interface CustomComponentProvider extends Mutable {
    String XML_TAG = "CustomComponentProvider";

    int CURRENT_LEVEL = 1;

    /**
     *
     *
     * @return
     */
    String getName();

    /**
     *
     *
     * @return
     */
}
```

```

String getType();

/**
 *
 *
 * @return
 */
String getIcon();

/**
 *
 *
 * @return
 */
String getPreviewIcon();

/**
 * html
 *
 * @param context
 * @return html
 */
String getEditPageHTML(OperationContext context);

/**
 * css js
 *
 * @param context
 * @return css js
 */
AssembleComponent editClient(OperationContext context);

/**
 * html
 *
 * @param context
 * @return html
 */
String getPreviewPageHTML(OperationContext context);

/**
 * css js
 *
 * @param context
 * @return css js
 */
AssembleComponent previewClient(OperationContext context);

String config();

/**
 *
 *
 * @param customComponentContext
 * @return
 */
boolean needDataProcess(CustomComponentContext customComponentContext);

/**
 * BI
 *
 * @param dataModels
 * @param customComponentContext
 * @return
 */
List<DataModel> process(List<DataModel> dataModels, CustomComponentContext customComponentContext);
}

```

bi.plugin.client.ts

```
import { BIPluginAction, BIPluginMessage } from '@webui/bi/plugin/bi.plugin.constant';

export class BIPluginClient {
  private connID: string | null = null;

  /**
   * datanull
   * config
   * saveSessionCallback(data: Object): Promise<json>
   * closeSessionCallbackBI
   * @param render
   */
  public init(
    render: (
      data: any,
      config: any,
      saveSessionCallback: (data: any) => Promise<any>,
      closeSessionCallback: () => void,
      extensionCallback?: (action: string, value: any) => void
    ) => void
  ): void {
    addEventListener('message', (event: MessageEvent) => {
      if (event.source === window.parent && event.data) {
        const eventData = JSON.parse(event.data);
        if (!this.connID && eventData.action === BIPluginAction.INIT) {
          this.connID = eventData.connID;
        } else {
          if (this.connID === eventData.connID && eventData.action === BIPluginAction.RENDER) {
            const { data, config } = eventData;
            render(
              data,
              config,
              this.saveSessionCallback.bind(this),
              this.closeSessionCallback.bind(this),
              this.extensionCallback.bind(this)
            );
          }
        }
      }
    });
  }

  private sendMessage(action: BIPluginAction, data: any, config?: any) {
    if (this.connID) {
      const message: BIPluginMessage = { connID: this.connID, action, data, config };
      parent.postMessage(JSON.stringify(message), '*');
    }
  }

  private saveSessionCallback(data: any): Promise<any> {
    return new Promise(resolve => {
      const saveListener = (event: MessageEvent) => {
        if (event.source === window.parent && event.data) {
          const eventData = JSON.parse(event.data);
          if (this.connID === eventData.connID && eventData.action === BIPluginAction.SAVE_COMPLETE) {
            removeEventListener('message', saveListener);
            resolve(eventData.data);
          }
        }
      };
      this.sendMessage(BIPluginAction.SAVE, data);
      addEventListener('message', saveListener);
    });
  }
}
```

```
private closeSessionCallback(): void {
    this.sendMessage(BIPluginAction.CLOSE, null);
}

private extensionCallback(action: string, value: any) {
    this.sendMessage(action, value);
}
}

// @ts-ignore
window.BIPlugin = BIPluginClient;
```

config.json json

dataModelfiledscolData
dataModelfields

BI	6.0.13-		

plugin.xml

```
<extra-core>
  <CustomComponentProvider class="your class name"/>
</extra-core>
```

FinePluginService
com.finebi.common.api.service.plugin.FinePluginService#getCustomComponentPagehtml
com.finebi.common.api.service.plugin.FinePluginService#getAllCustomComponentInfoname

demo[plugin-bi-custom-chart-demo](#)